

ERO-TEX

THE GROUND CONTROL LEADERS

Dewatering Filter Bag



ERO-TEX dewatering filter bags are effective in collecting sediment from dewatering operations. Sediment-laden water is pumped into the bag.

ERO-TEX dewatering filter bags should be placed on a level area. (Bags can roll down slopes.) Insert pumps discharge hose into bag and secure the connection with clamp or tie wire.

ERO-TEX filter bags can handle most applications utilizing 2"-4" discharge hose.

Options: Made from 8oz. nonwoven needle-punched geotextile with double stitched seams, the fabric has an AOS of 70 US sieve and 100 gpm/ft² water flow, **ERO-TEX** dewatering filter bags are strong and permeable. NOTE: High pumping rates and high sediment loads can cause the bag to burst.

Sizes: 10'x15' for 2" discharge hose.
20'x15' for 3" discharge hose.
25'x15' for 4" discharge hose.
35'x15' for 6" discharge hose.

ERO-TEX

THE GROUND CONTROL LEADERS

866 437-6839 toll free

Warehouse locations:

Itasca IL

Little Chute WI

Menomonee Falls WI

Morton IL

Wisconsin Rapids WI

ERO-TEX

N94 W14330

Garwin Mace Drive

Menomonee Falls WI

53051